

Polycom SoundStation® IP 3000 - 3Com® NBX

Polycom's Voice over IP conference phone for NBX Networked Telephony Solutions.



Product Data Sheet
Voice

Feature Highlights:

Fully compatible—works seamlessly with SuperStack® 3 NBX and NBX 100 Networked Telephony Solutions.

Graphical LCD display—easy-to-use, easily readable and intuitive interface gives access to rich 3Com telephony feature set.

Full-duplex operation—Clarity by Polycom™ technology permits natural, two-way, hands-free conversations without clipping or distortion.

360-degree room coverage—a powerful, digitally-tuned custom speaker and three sensitive microphones provide uniform coverage of a small to medium-sized conference room or office.

Single-cable design—cable combines network and power wiring to reduce clutter to the tabletop.

Simple to install—install the 3Com - Polycom license* in your NBX system and customize the phone as you desire.

Downloadable upgrades—upgrade in the field for software updates to protect your investment.

* Sold Separately

SoundStation IP, Polycom's first "pure IP" full-duplex conference phone is now available for NBX systems.

The SoundStation IP 3000 - 3Com NBX now offers NBX users the same Clarity by Polycom technology that has made us the leader in audioconferencing. The promise of single-network communications is now fulfilled in the conference room. No more special analog lines and/or Analog Terminal Adapters. Simply plug the SoundStation IP 3000 - 3Com NBX into your Ethernet network and gather around the table for your conference call.



Welcome to the "converged" world of Voice over IP (VoIP).

The SoundStation IP 3000 - 3Com NBX is ready to take on the VoIP world. Whether you have a large group around the conference room table or you need to work hands-free at your desk, the SoundStation IP 3000 - 3Com NBX lets you communicate "as naturally as being there".

To learn more about how Polycom is helping to shape the IP world of tomorrow, visit our Web site at: www.polycom.com.

Polycom SoundStation IP 3000 - 3Com NBX

Product Features

Full-duplex Echo Cancellation

User selectable ringer tones

IP Address Configuration

Multiple Call Appearances

Convenient volume adjustment keys

— DHCP

Local Speed Dials

Caller ID (if available)

— Static IP



Business Telephony Features including:

— Hold

— Call Transfer

— Conferencing

— Call Park

— Redial

— Mute

Easily upgrade SoundStation IP 3000 - 3Com NBX in the field

— Trouble-free software maintenance

— Extends the life of the product to protect your investment

Auto-discovery enables effortless installation and easy moves, adds, and changes

QoS support includes 802.1p and IP-ToS

Conference phone can operate as either a Layer 2 or Layer 3 (IP) device

Technical Specifications

Size

2.5 x 12 x 2.25 in
(31.5 x 30.2 x 5.7 cm) (WxHxD)

Regulatory Compliance

Safety

— UL1950

— CSA C22.2, No. 950

— EN60950

— IEC60950

— AS/NZS3260

EMC

— FCC (47 CFR Part 15) Class B

— ICES-003 Class B

— EN55022 Class B

— CISPR22 Class B

— AS/NZS 3548 Class B

— VCCI Class B

— EN50224

SoundStation IP 3000 - 3Com NBX ships with:

— Quick reference guide

— User manual

— Warranty registration card

— Tabletop console with integrated display and keypad

— Power Interface Module (PIM)

— Universal power supply brick

— 6 ft Cat 5 Ethernet cable

— 25 ft Power/Ethernet cable (Connects PIM to console)

Warranty

12 months

Environment Conditions

Operating temperature: 32° - 104°F (0° - 40°C)

Relative humidity: 20% - 85% (non-condensing)

Storage temperature: -22° - 131°F (-30° - 55°C)

Part Number

2200-06632-001

Specifications subject to change without notice.



www.polycom.com

Polycom, Inc. • 1565 Barber Lane • Milpitas, CA 95035
1.800.POLYCOM • 1.408.526.9000 • Fax 1.408.526.9100

© 2001 Polycom, Inc. All rights reserved. Polycom, SoundStation, SoundPoint, and the Polycom logo design are registered trademarks of Polycom, Inc. in the U.S. and various countries. 3Com, NBX, and SuperStack are registered trademarks of 3Com Corporation. All other trademarks are the property of their respective companies. Specifications subject to change without notice.

Part No. 3726-7255-001 Rev. 12/01